

## Features

- Universal Input Voltage Range 100-240V AC
- Approved to UL, CB, CE, UKCA, TUV, FCC, RoHS & REACH
- IEC/EN/UL 62368-1 Safety Approved
- Level VI Efficiency
- Means of Protection : 2 X MOPP
- Single Output 12-56V DC
- P.D. 3.0 / QC 4.0+ / QC 4.0



## 44ATS120TS-PXXX Series

120W GaN FET AC/DC Desktop Power Supply



The 44ATS120TS-PXXX Series is a performance-focused External Power Supply (PSU)>PD & GaN Power Supply. Designed for use in applications such as network equipment and signal distribution hardware. This series is supplied with a C14 input connection and supports input voltages of 100~240V AC 50~60Hz.

### Model Number Information

44ATS120TS-P **XXX**

Series Name **voltage**

### Models

Model Number	DC Voltage (V)	Rated Current (A)	Rated Power (W)	Efficiency (%)
44ATS120TS-P120	12	9	108	88
44ATS120TS-P190	19	6.3	120	88
44ATS120TS-P200	20	6	120	88
44ATS120TS-P240	24	5	120	88
44ATS120TS-P480	48	2.5	120	88
44ATS120TS-P560	56	2.14	120	88

## Input Specifications

Rated Voltage Range	100-240VAC
Frequency Range	50/60Hz
AC Current	1.6A Max.
Efficiency	Meet DoE Level VI, ErP Stage 2, CoC Tier 2
Configuration	≤ 1% Vp-p @ Full Load

## Output Specifications

Load Regulation	±5% ( Typical )
Ripple & Noise	≤ 100m Vp-p @ Full Load
Transient (Dynamic) Response	0.5mS with 50% Load Change
Start-up Time	< 3,000mS
Hold-up Time	≥ 10mS @ Full Load
Rise Time	< 50mS

## Protection

Protection 1	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection
Protection 2	Internal Primary Current Fuse

## Environmental Characteristics

Working Temp	-20 ~ +40°C
Working Humidity	20 ~ 80%RH
Storage Humidity	-10 ~ 90% RH
Storage Temperature	-20 to + 80°C
Operating Altitude	5,000M
Cooling	Natural Convection Cooling

## Electrical

Topology	LLC
Dielectric Withstand	3,000VAC Primary - Secondary
Earth Leakage Current	< 5mA
MTBF	300,000 Calculated Hours at 25°C by Telcordia SR-332,
EMC Standards	EN55032 EN61000-3-2,3 EN55035

## Dimensions & Weight

	Measurements	Weight
44ATS120TS-PXXX	132×51×32mm	336g

## Derating Curves

