

Features

- Universal Input 90~264VAC 50/60Hz
- Ultra Slim Step Line
- High Efficiency
- Low Ripple & Noise
- Class II Isolation
- Protection: OLP, OVP, SCP
- 3 years warranty



Ideal Power's 56YSD60S-xy 60W DIN Rail Mount AC/DC Power Supply Converter Series are certified to cURus, CE, RoHS & IEC/UL/EN62368 Standards and comply with (EU) 2019/1782, Level VI Efficiency Regulations. These are primarily used in ITE, Audio & Video Industries and customised solutions are available upon request.

Models

Model Number	Output Voltage (V DC)	Voltage Adj. Range (V)	Output Current (A)	Output Power (W)	Efficiency (%)	Ripple & Noise (mVp-p)
56YSD60S-1204500	12	5~5.5	4.5	54	88	120
56YSD60S-1504000	15	13.5~18	4	60	89	120
56YSD60S-2402500	24	21.6~29	2.5	60	90	150
56YSD60S-4801250	48	43.2~55.2	1.25	60	91	240

Input Specifications

Input Electrical Phase	Single
Line Frequency	47-63Hz
Inrush Current	30 Amps max. at 115VAC/60Hz, full load & 60Amps max. at 240VAC/50Hz, full load
AC Current	1.2A/115VAC 0.8A/230VAC
Efficiency Type	88~91% Depending on Model
Leakage Current	<0.25mA/240VAC

Output Specifications

Output Voltage Adjustment	+/- 10% Depending on Model
Ripple and Noise	120~240 mV Depending on Model
Line Regulation	± 1%
Load Regulation	± 1%
Isolation Resistance	I/P-O/P: 100M Ohms / 500VDC / 25 / 70% RH
Setup, Rise, Hold Up time	500mS/50mS/12mS (115V/60HZ MAX ROAD), 500mS/50mS/30mS (230V/50HZ MAX ROAD)
MTBF	200000 h

General Specification

Type	DIN Rail Power Supply
AC or DC Input Voltage	AC
AC or DC Output Voltage	DC
Number of Outputs	1
Mounting Style	Din Rail Mount
Connection Type	Screw Terminal Type
Overload Protection	>130%-200% rated output power (Protection type: Hiccup mode, recovers automatically after fault condition is removed)
Over Current Protection	110% - 180%
Short Circuit Protection	Protection to Zero Voltage
Over Voltage Protection	110~145% (Protection Type: Clamp by zener diode)

Operational Environment

Operating Humidity	20% ~ 90% RH non-condensing
Operating Temperature Range	-20°C to 50°C, Full load, Normal operation.
Storage Temperature Range	-40°C to 80°C
Storage Humidity	10% ~ 95% RH
Cooling	Cooling

Approvals

Safety Standard	UL60950-1, UL508, , BSMI CNS14336-1, TUV EN61558-2-16 IEC60950-1, EAC TPTC 004, TUV EN60950-1
EMC Emissions	EN55032(CISPR32), CNS13438 Class B , EN61000-3-2 Class A , EN61000-3-3, EN61000-4- 2,3,4,5,6,8,11, EN55024, EN55035, EN61000-6-2, EN61204-3

Mechanical Specifications



Housing Material	Fully Enclosed Plastic Case
Overall Dimensions	58mm x 52.5mm x 90mm
Overall Length	90mm
Overall Depth	58mm
Overall Width	52.5mm
Weight	190g

Protection Category


IP Rating	IP20
-----------	------

Mechanical Drawing

■ Dimensions and Installation:



■ Deduction curve and temperature:



■ Minus output and input voltage curves:

