


1W, Wide input voltage, isolated & regulated output DC/DC converter



CE Patent Protection **RoHS**

FEATURES

- Ultra compact SIP package
- Wide input voltage range (2:1)
- Operating temperature range: -40°C to +85°C
- Isolation voltage: 1.5K VDC
- Low ripple & noise
- Short circuit protection (self-recovery)
- Remote On/Off
- EN60950 approval

36WRA_S-1WR2 & 36WRB_S-1WR2 series are isolated 1W DC-DC products with 2:1 input voltage and conventional voltage output. The product has a relatively compact SIP-8 plastic package, and features high efficiency, operating temperature of -40 °C~+85 °C, remote control, and continuous short-circuit protection. The smaller size and fine cost design make the converter an ideal solution in communication, instruments, and industrial electronics applications.

Selection Guide

Certification	Part No.	Input Voltage (VDC)		Output		Ripple & Noise (mVp-p, Typ./Max.)	Efficiency (% Min./Typ.) @ Full Load	Max. Capacitive Load ² (µF)
		Nominal (Range)	Max. ①	Output Voltage(VDC)	Output Current (mA)(Max./Min.)			
CE	36WRA0505S-1WR2	5 (4.5-9)	11	±5	±100/±5	70/100	71/73	1000
	36WRA0512S-1WR2			±12	±42/±2		74/76	470
	36WRA0515S-1WR2			±15	±33/±2		73/75	330
	36WRB0503S-1WR2			3.3	303/15		69/71	1800
	36WRB0505S-1WR2			5	200/10		70/72	2200
	36WRB0512S-1WR2			12	83/4		74/76	1000
	36WRB0515S-1WR2			15	67/3		73/75	680
	36WRB0524S-1WR2			24	42/2		71/73	470
	36WRA1205S-1WR2	12 (9-18)	20	±5	±100/±5	100/150	76/78	1000
	36WRA1212S-1WR2			±12	±42/±2		79/81	470
	36WRA1215S-1WR2			±15	±33/±2		76/78	330
	36WRB1203S-1WR2			3.3	303/15		73/75	2700
	36WRB1205S-1WR2			5	200/10		75/77	2200
	36WRB1209S-1WR2			9	111/6		77/79	1800
	36WRB1212S-1WR2			12	83/4		77/79	1000
	36WRB1215S-1WR2			15	67/3		78/80	680
	36WRB1224S-1WR2	24	42/2	74/76	470			
	36WRA2405S-1WR2	24 (18-36)	40	±5	±100/±5	70/100	77/79	1000
	36WRA2409S-1WR2			±9	±56/±3		77/79	680
	36WRA2412S-1WR2			±12	±42/±2		77/79	470
	36WRA2415S-1WR2			±15	±33/±2		77/79	330
	36WRB2403S-1WR2			3.3	303/15		73/75	2700
	36WRB2405S-1WR2			5	200/10		75/77	2200
	36WRB2412S-1WR2			12	83/4		76/78	1000
	36WRB2415S-1WR2			15	67/3		76/78	680
	36WRB2424S-1WR2	24	42/2	75/77	470			
	36WRA4805S-1WR2	48 (36-75)	80	±5	±100/±5	100/150	74/76	1000
	36WRA4812S-1WR2			±12	±42/±2		76/78	470
	36WRA4815S-1WR2			±15	±33/±2		78/80	330
	36WRB4803S-1WR2			3.3	303/15		73/75	2700

CE	36WRB4805S-1WR2	48 (36-75)	80	5	200/10	100/150	74/76	2200
	36WRB4812S-1WR2			12	83/4		78/80	1000
	36WRB4815S-1WR2			15	67/3		77/79	680

Notes: ①Exceeding the maximum input voltage may cause permanent damage;
②For the dual output modules, the capacitive loads of positive and negative outputs are the same.

Input Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Input Current (full load/no-load)	5VDC Input	--	281/40	290/60	mA
	12VDC Input	--	111/15	114/30	
	24VDC Input	--	55/6	57/10	mA
	48VDC Input	--	27/4	28/6	
Reflected Ripple Current	5VDC Input	--	30	--	mA
	12VDC Input	--	40	--	
	24VDC Input	--	55	--	
	48VDC Input	--	45	--	
Input Impulse Voltage (1sec. max.)	5VDC Input	-0.7	--	12	VDC
	12VDC Input	-0.7	--	25	
	24VDC Input	-0.7	--	50	
	48VDC Input	-0.7	--	100	
Starting Voltage	5VDC Input	--	--	4.5	VDC
	12VDC Input	--	--	9	
	24VDC Input	--	--	18	
	48VDC Input	--	--	36	
Input Filter		Filter capacitor			
Hot Plug		Unavailable			
Ctrl*	Module turn-on	The Ctrl end is suspended or of high resistance			
	Module turn-off	Connect with high level (relative to the input grounding) to make the 5-10mA current flows into the Ctrl end.			

Note: * For use of Ctrl, please refer to the "design reference" in this manual.

Output Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit	
Output Voltage Accuracy	5%-100% load, Input voltage range	3.3V/5V output	--	±2	±5	%
		others	--	±1	±3	
No-load Output Voltage Accuracy	Input voltage range	--	±1.5	±5		
Balance of Output Voltage	Dual output, balanced load	--	±0.3	±0.5		
Line Regulation	Full load, the input voltage is from low to high	--	±0.2	±0.5		
Load Regulation	5%-100% load	--	±0.4	±0.75		
Transient Recovery Time	25% load step change	--	0.5	2	ms	
Transient Response Deviation		--	±2.5	±5	%	
Temperature Coefficient	Full load	--	±0.02	±0.03	%/°C	
Short Circuit Protection		Continuous, self-recovery				

Note: *Ripple and noise are measured by "parallel cable" method, please see DC-DC Converter Application Notes for specific operation.

General Specifications

Item	Operating Conditions	Min.	Typ.	Max.	Unit
Isolation Voltage	Input-output, with the test time of 1 minute and the leak current lower than 1mA	1500	--	--	VDC
Isolation Resistance	Input-output, isolation voltage 500VDC	1000	--	--	MΩ
Isolation Capacitance	Input-output, 100KHz/0.1V	--	120	--	pF

Operating Temperature	Derating if the temperature $\geq 85^{\circ}\text{C}$, (see Fig. 1)	-40	--	85	°C
Storage Temperature		-55	--	125	
Pin Welding Resistance Temperature	Welding spot is 1.5mm away from the casing, 10 seconds	--	--	300	
Storage Humidity	Non-condensing	--	--	95	%RH
Switching Frequency (PFM Mode)	Full load, nominal input voltage	--	200	--	KHz
MTBF	MIL-HDBK-217F@25°C	1000	--	--	K hours

Physical Specifications


Casing Material	Black flame-retardant and heat-resistant plastic (UL94-V0)
Dimension	22.00*9.50*12.00 mm
Weight	4.90g(Typ.)
Cooling Method	Free convection

EMC Specifications


EMI	CE	CISPR22/EN55022 CLASS B (see Fig. 3-② for recommended circuit)
	RE	CISPR22/EN55022 CLASS B (see Fig. 3-② for recommended circuit)
EMS	ESD	IEC/EN61000-4-2 Contact $\pm 4\text{KV}$ perf. Criteria B
	RS	IEC/EN61000-4-3 10V/m perf. Criteria A
	EFT	IEC/EN61000-4-4 $\pm 2\text{KV}$ (see Fig. 3-① for recommended circuit) perf. Criteria B
	Surge	IEC/EN61000-4-5 $\pm 2\text{KV}$ (see Fig. 3-① for recommended circuit) perf. Criteria B
	CS	IEC/EN61000-4-6 3 Vr.m.s perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-29 0%-70% perf. Criteria B

Product Characteristic Curve


Temperature Derating Curve





Efficiency Vs Input Voltage (Full Load)



Efficiency Vs Output Load (Vin=24V)






Design Reference

1. Recommended circuit

All the DC/DC converters of this series are tested according to the recommended circuit (see Fig. 2) before delivery.

If a further decrease of the input and output ripple is required, properly increase the input & output of additional capacitors Cin1, Cin2, Cs and Cout; or select capacitors of low equivalent impedance like series capacitor, etc. Cs is used to reduce ripple. No need to add Cs, if ripple meets the demand. Appropriate filter capacitance shall be chosen, start-up problems may be caused if the capacitance is too large. For each output circuit, under the condition of safe and reliable operation, the max. capacity of its filter capacitor should be lower than the max. capacitive load.

Single



Dual




Fig. 2

Vin	5VDC&12VDC	24VDC&48VDC
Cin1	100μF	10μF
Cin2	47μF	1μF
Lin	4.7μH~12μH	
Cs	10μF~22μF	
Cout	100μF(Typ.)	
Lout	2.2μH~10μH	
Cd	47nF/100V	

2. EMC solution-recommended circuit




Fig. 3

Parameter description:

Model	Vin:5VDC	Vin:12VDC	Vin:24VDC	Vin:48VDC
FUSE	Slow blown fuses according to the actual input current selections of the clients			
MOV	--	S14K25	S14K35	S14K60
C0	1000μF/16V	1000μF/25V	330μF/50V	330μF/100V
C1	4.7μF/50V			4.7μF/100V
LDM1	12μH			
C2	4.7μF/50V			4.7μF/100V
C3	Refer to the Cout in Fig.2			
CY1	1nF/2KV			
D1	RB160M-60/1A			
R	In accordance with the formula: $R = \frac{V_C - V_D - 1.0}{I_C} - 300$			
Cd	47nF/100V			

Notes:

VAT No. GB 771 1607 40

Registered in England No. 4063412

Weee Reg. WEE/DD0749YY

+44 (0) 845 260 3400


enquiries@idealpower.co.uk

idealpower.co.uk

Ideal Power Ltd.
14 Larks Way
Tree Beech Enterprise Park
Gunn, Barnstaple
Devon, EX32 7NZ
England, UK

- ① Part ① in Fig. 3 is used for EMS test while part ② is used for EMI filtering; and parts ① and ② may be selected based on needs.
- ② V_C is the voltage of the Ctrl end relative to the GND of the input grounding; V_D is the positive-going conduction pressure drop of D1; I_C is the current flows into the Ctrl end and its value is generally 5-10mA, see Fig. 3-③ for the peripheral circuit of Ctrl end;
- ③ If there is no recommended parameters, no external component is required.

EMC solution-recommended circuit PCB layout



Note: the min. distance of the bonding pads between input grounding and output grounding shall be $\geq 2\text{mm}$.

3. Ctrl end

The modules are of normal output when the Ctrl end is suspended or of high resistance; the modules turn off when connecting with high level (relative to the input grounding); notice that the current flows into the pin shall be 5 - 10mA, the modules will be permanently damaged if the current exceeds its max. value (20mA in general).

The value of R can be derived as follows:

$$R = \frac{V_C - V_D - 1.0}{I_C} - 300$$

For Detailed parameter, please refer to EMC solution-recommended circuit in this manual.

4. Input current

When the electricity is provided by the unstable power supply, please make sure that the range of the output voltage fluctuation and the ripple voltage of the power supply do not exceed the indicators of the modules. Input current of power supply should afford the flash startup current of this kind of DC/DC module (see Fig. 5).

Generally: Vin= 5V series	lave =445mA
Vin=12V series	lave =205mA
Vin=24V series	lave =104mA
Vin=48V series	lave =53mA





Fig. 5

5. Output load requirements

When using, the minimum load of the module output should not be less than 5% of the nominal load. In order to meet the performance parameters of this datasheet, please connect a 5% dummy load in parallel at the output end, the dummy load is generally a resistor, please note that the resistor needs to be used in derating.

6. For more information please find DC-DC converter application notes on www.idealpower.co.uk

Dimensions and Recommended Layout



Notes:

1. Recommend to use module with more than 5% load, if not, the ripple of the product may exceeds the specification, but does not affect the reliability of the product;
2. The recommended unbalance degree of the dual output module load is $\pm 5\%$; if the degree exceeds $\pm 5\%$, than the product performance cannot be guaranteed to comply with all parameters in the datasheet. Please contact our technicians directly for specific information;
3. The maximum capacitive load offered were tested at nominal input voltage and full load;
4. Unless otherwise specified, parameters in this datasheet were measured under the conditions of $T_a=25^\circ\text{C}$, humidity<75% with nominal input voltage and rated output load;
5. All index testing methods in this datasheet are based on Company's corporate standards;
6. The performance parameters of the product models listed in this manual are as above, but some parameters of non-standard model products may exceed the requirements mentioned above. Please contact our technicians directly for specific information;
7. We can provide product customization service;
8. Specifications-are subject to change without prior notice.